## AUTOMATIC STERILIZER | AUTOCLAVE

## **Standard Accessories**

- ≻ Mail Unit
- Instruction manual
- Instrument tray rack
- Instrument tray
- Power cod
- ≻ Main board fuse
- Water outlet tube
- Tray holder
- ≻ Filterable net
- Sealing ring
- ≻ Fuse

**Distinct Feature** 

- Draining O ring
- Level instrument
- Door adjustment spanner
- Optional Printer

Dry procedure: Vacuum drying





	Model	8L-LCD/8L-LED	I2L-L	CD/12L-LED	17L-LCD/17L-	LED	22L-LCD/22L-LED	
	Chamber Volume	Ö170x310mm	Ö2	00x355mm	Ö250x355mn	n	Ö 250x450mm	
)	Sterilization Temperature/ Pressure	121 ? (1.0-1.3)bar (Standard Atmosphere Pressure) 134 ? (2.0-2.4)bar (Standard Atmosphere Pressure)						
	Safety Design	Safety valve, Interlock door, Sensors protection						
	Dimension	660x480x470mm		Dry c <b>700x350</b> 0	<b>185mm</b> lave drying	cycle	755x625x550mm	
	Power	ver 220V/50Hz, 1400W		220V/50Hz, 1800W		220V/50Hz, 2300W		
	Weight	50kgs		56kgs		59kgs		



Sterilizing record: Micro-printer (recording the whole process) diagnosing & alarm system Water supply system: Reservoirs (3.5L fresh water & 5L waste water)

Safety Features: Pressure release valve and computerize

## Vertical Pressure Steam Sterilizer | Autoclave

## Silent Features

- > Whole body inner and outer by stainless steel.
- Hand wheel type of quick-open door structure.
- Door safety locks system.
- > Digital display of working status, touch of key
- > With two stainless steel sterilizing baskets.
- > Over temperature & over pressure auto-protection
- Safe protection of water lacking
- Self-inflating type seal
- Automatically shut off with beep reminding after sterilization
- > Auto-letting off the cool air, and steam discharging automatically after sterilization

Model	LS-B35L	LS-B50L	LS-B75L			
Chamber Volume	35L	50L	75L			
Chamber dimension	ö318x450mm	ö340x550mm	ö400x600mm			
Outer dimension	450x450x1010 mm	480x490x1030 mm	540x630x1300 mm			
Temperature scope						
Pressure scope						
Heat average	=±1°C					
Timer scope	cope 0-99min					
Safety	door safety look system					
Power	220V/50Hz, 2.5 KW	220V/50Hz, 3KW	220V/50Hz,4.5KW			
Weight	50kgs	55kgs	82kgs			

Standard accessories Mail Unit, Instruction manual, Basket SS, Clamps